
(19) 

**Canadian
Intellectual Property
Office**

An Agency of
Industry Canada

**Office de la Propriété
Intellectuelle
du Canada**

Un organisme
d'industrie Canada

(11) **CA 323400** (13) **A**

(40) **21.06.1932**

(12)

(21) Application number: **323400D**

(51) Int. Cl:

(22) Date of filing: ..

(71) Applicant: **KEGRESSE ADOLPHE.**

(72) Inventor: **KEGRESSE ADOLPHE ().**

(54) **MOTOR VEHICLE TRUCK**

(57) **Abstract:**

(54) **TRAIN DE VEHICULE-MOTEUR**

This First Page has been artificially created and is not part of the CIPO Official Publication

2


THIS IS THE EXHIBIT MARKED
 PREPARED TO IN THE AFFIDAVIT OF

Adolphe Kerpene

SWORN BEFORE ME THIS 9th DAY OF
 March, 1930

R. Q. Joseph

Notary Public for the State of
 Illinois



It is easily understood that it is of great interest to realize an endless strip driving gear of reduced dimensions, and having, at the same time, as great a surface of contact with the ground as possible.

The present invention relates to a new combination of known devices, providing such endless strip gear.

Two embodiments of the invention are shown, by way of example, in the appended drawing.

Figure 1 is a diagrammatical elevational view of the device with a two roller bogie.

Figure 2 is a similar device, wherein the bogie is a one roller bogie.

Figure 3 is a plan view of the first device.

Throughout these figures, 1 represents the carrying axle of the vehicle part corresponding to the endless strip driving apparatus.

This axle 1 is secured to the frame in a known manner by means of two longitudinal springs 2 (figures 1 and 2).

Suitably shaped carrying equalizers 3 are adjustably mounted on each end of axle 1. These equalizers receive, at the end of their bigger arms, one of the supporting pulleys of the caterpillar 4 (figures 1, 2, 3), and at their other end an articulation 5 of the two roller bogie 6 (figures 1 and 3) or a single roller 7 (figure 2).

4

The articulation point of the equalizers 3 on axle 1 is selected so that the load should conveniently be distributed between one of the supporting pulleys 4 of the endless strips and the roller or rollers 6 and 7.


A carrying arrangement is thus obtained having a maximum surface of contact with the ground responsive to an extremely reduced total length.

HAVING thus described my invention, I claim:-

1. In a truck having endless belt driving means, a carrying axle, elastic means securing said axle to a frame, pulleys supporting the endless belt, roller means adapted to receive a part of the load on the truck, and an equaliser at each end of the carrying axle for distributing the load between the belt pulleys and the roller means.

2. A truck as claimed in claim 1, wherein the roller means comprise a bogie having one or more rollers.

Fig 1.




Certified to be the drawings referred to
in the specification hereunto annexed.
MONTREAL, December 26, 1930.

ADOLPHE REGRESSO,
Inventor,

By

Maxime Maxion
Attorneys.



Certified to be the drawings referred to in the specification hereunto annexed.

ADOLPHE KEGRESSE,
Inventor,

BY


MONTREAL, December 26, 1930.

Attorneys.

97

323400

Fig. 3.



Certified to be the drawings
referred to in the specification
hereunto annexed.

MONTREAL, December 26, 1930.

ADOLPHE KEGRESSE,
Inventor

By

Maxime Maxier

Attorneys.